



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G03F 9/00, G06F 17/00, 17/50		A1	(41) International Publication Number: WO 99/14636 (43) International Publication Date: 25 March 1999 (25.03.99)
(21) International Application Number: PCT/US98/19438 (22) International Filing Date: 17 September 1998 (17.09.98) (30) Priority Data: 60/059,306 17 September 1997 (17.09.97) US 08/931,921 17 September 1997 (17.09.97) US 60/069,549 12 December 1997 (12.12.97) US 09/130,996 7 August 1998 (07.08.98) US Not furnished 16 September 1998 (16.09.98) US Not furnished 16 September 1998 (16.09.98) US		(71) Applicant (for all designated States except US): NUMERICAL TECHNOLOGIES, INC. [US/US]; Suite 100, 2630 Walsh Avenue, Santa Clara, CA 95051 (US). (72) Inventors; and (75) Inventors/Applicants (for US only): CHANG, Fang-Cheng [US/US]; 2434 Rock Street #9, Mountain View, CA 94043 (US). WANG, Yao-Ting [-/US]; 970 Corte Madera Avenue #311, Sunnyvale, CA 94086 (US). PATT, Yagyensh, C. [US/US]; 816 Amber Lane, Los Altos, CA 94024 (US). (74) Agent: RICHARDSON, Kent. R.; Wilson Sonsini Goodrich & Rosati, 650 Page Mill Road, Palo Alto, CA 94304-1050 (US). (81) Designated States: AL, AM, AT, AU, AZ, BA, BR, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(63) Related by Continuation (CON) or Continuation-in-Part (CIP) to Earlier Applications US 60/059,306 (CIP) Filed on 17 September 1997 (17.09.97) US 08/931,921 (CIP) Filed on 17 September 1997 (17.09.97) US 60/069,549 (CIP) Filed on 12 December 1997 (12.12.97) US 09/130,996 (CIP) Filed on 7 August 1998 (07.08.98) US Not furnished (CIP) Filed on 16 September 1998 (16.09.98) US Not furnished (CIP) Filed on 16 September 1998 (16.09.98)		Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	
(54) Title: METHOD AND APPARATUS FOR DATA HIERARCHY MAINTENANCE IN A SYSTEM FOR MASK DESCRIPTION			
(57) Abstract <p>A method and apparatus for performing an operation on hierarchically described integrated circuit layouts (800) such that the original hierarchy of the layout is maintained is provided. The method comprises providing a hierarchically described layout (810) as a first input and providing a particular set of operating criteria (840) corresponding to the operation to be performed as a second input. The mask operation, which may include operations such as OPC and logical operations such as NOT and OR (240), is then performed on the layout in accordance with the particular set of operating criteria. A first program data comprising hierarchically configured correction data corresponding to the hierarchically described layout is then generated in response to the layout operation such that if the first program data (860) was applied to the flattened layout (865) an output comprising data representative of the result of performing the operation on the layout would be generated. As the first program data is maintained in a true hierarchical format, layouts which are operated upon in accordance with this method are able to be processed through conventional design rule checkers (850). Further, this method is capable of being applied to all types of layouts including light and dark field designs and phase shifting layouts.</p>			
<pre> graph TD 800[Chip Design 800] --> 810[(Hierarchical Design Data 810)] 810 --> 210[Hierarchy Preserver 210] subgraph 210 [Hierarchy Preserver 210] 220[Compiler 220] 230[Logic 230] end 220 --> 840[Computer Running OPC Algorithm 840] 220 --> 240[OPC Operation Engine 240] 230 --> 240 240 --> 845[(Hierarchical Correction Data 845)] 845 --> 850[Design Rule Checker 850] 850 --> 860[Combine Design Data with Correction Data 860] 860 --> 865[Flatten Data and Write to EB Machine 865] 865 --> 870[Produce Mask 870] 870 --> MP[Mask Production] </pre>			

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TC	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
HJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

**METHOD AND APPARATUS FOR DATA HIERARCHY MAINTENANCE
IN A SYSTEM FOR MASK DESCRIPTION**

5

1. Related Applications

This application relates to, claims benefit of the filing date of, and incorporates by reference, the United States provisional patent application entitled "Data Hierarchy Advanced Mask Correction and Verification Method and Apparatus," having serial number 60/069,549, filed on December 12, 1997, and invented by Fang-Cheng Chang, Yao-Ting Wang and Yagyensh C. Pati. Further, this application relates to and incorporates by reference, the United States provisional patent application entitled, "Mask Verification, Correction, and Design Rule Checking" having serial number 60/059,306, filed September 17, 1997, and invented by Fang-Cheng Chang, Yao-Ting Wang and Yagyensh C. Pati and United States patent application entitled, "Mask Verification, Correction, and Design Rule Checking", filed September 16, 1998, and invented by Fang-Cheng Chang, Yao-Ting Wang and Yagyensh C. Pati. This application also relates to and incorporates by reference the United States patent application entitled "Visual Inspection and Verification System", filed August 7, 1998, and invented by Fang-Cheng Chang, Yao-Ting Wang, Yagyensh C. Pati, and Linard Karklin.. This application also relates to and incorporates by reference, the United States patent application entitled, "Phase Shifting Circuit Manufacture Method and Apparatus" having serial number 08/931,921, filed September 17, 1997, and invented by Yao-Ting Wang and Yagyensh C. Pati. Each of the aforementioned patents are assigned to the assignee of the present invention.

2. The Background of the Invention

a. The Field of the Invention

This invention relates to the field of integrated circuit manufacturing. In

particular, the invention relates to concepts and implementation techniques for the quick and efficient design, correction and verification of masks utilized in the manufacture of integrated circuits.

5 b. Description of Related Art

 In designing an integrated circuit (IC), engineers typically rely upon computer simulation tools to help create a circuit schematic design consisting of individual devices coupled together to perform a certain function. To actually fabricate this circuit in a semiconductor substrate the circuit must be translated
10 into a physical representation, or layout, which itself can then be transferred onto the silicon surface. Again, computer aided design (CAD) tools assist layout designers in the task of translating the discrete circuit elements into shapes which will embody the devices themselves in the completed IC. These shapes make up the individual components of the circuit, such as gate
15 electrodes, field oxidation regions, diffusion regions, metal interconnections, and so on.

 The software programs employed by these CAD systems are usually structured to function under a set of predetermined design rules in order to produce a functional circuit. Often, these rules are determined by certain
20 processing and design limitations. For example, design rules may define the space tolerance between devices or interconnect lines so as to ensure that the devices or lines do not interact with one another in any unwanted manner. Design rule limitations are frequently referred to as critical dimensions. A critical dimension of a circuit is commonly defined as the smallest width of a
25 line or the smallest space between two lines. Consequently, the critical dimension determines the overall size and density of the IC. In present IC technology, the smallest critical dimension for state-of-the-art circuits is approximately 0.25 microns for line widths and spacings.

 Once the layout of the circuit has been created, the next step to
30 manufacturing the integrated circuit (IC) is to transfer the layout onto a

semiconductor substrate. Optical lithography is a well known process for transferring geometric shapes onto the surface of a silicon wafer. The optical lithography process generally begins with the formation of a photoresist layer on the top surface of a semiconductor wafer. A mask having fully light non-transmissive opaque regions, which are usually formed of chrome, and fully light transmissive clear regions, which are usually formed of quartz, is then positioned over the photoresist coated wafer. Light is then shone on the mask via a visible light source or an ultra-violet light source. The light is focused to generate a reduced mask image on the wafer typically using an optical lens system which contains one or several lenses, filters, and or mirrors. This light passes through the clear regions of the mask to expose the underlying photoresist layer, and is blocked by the opaque regions of the mask, leaving that underlying portion of the photoresist layer unexposed. The exposed photoresist layer is then developed, typically through chemical removal of the exposed/non-exposed regions of the photoresist layer. The end result is a semiconductor wafer coated with a photoresist layer exhibiting a desired pattern which defines the geometries, features, lines and shapes of that layer. This pattern can then be used for etching underlying regions of the wafer.

Besides the aforementioned design rules, the resolution value of the exposure tool used in optical lithography also places limits on the designers of integrated circuit layouts. The resolution for an exposure tool is defined as the minimum feature that the exposure tool can repeatedly expose onto the wafer. Currently, the resolution for most advanced optical exposure tools is around 0.25 micron. As the critical dimensions of the layout become smaller and approach the resolution value of the lithography equipment, the consistency between the mask and the actual layout pattern developed in the photoresist is significantly reduced. Specifically, it is observed that differences in pattern development of circuit features depends upon the proximity of the features to one another.

With these limitations on IC design in mind, we note the data describing

an IC pattern is usually represented in a condensed hierarchical fashion such as in a GDS-II data file. At the higher levels of pattern representation hierarchy, features are represented in a conceptual manner. For instance, a memory array may be described as having a given cell repeated for a certain number of rows and columns. The next lower level in the hierarchy might describe the basic memory cell, comprised of subcells A and B. Finally, at the lowest level, the most primitive subcells contain geometric primitives-rectangles and polygons. In order to generate a physical mask, the hierarchical data must first be flattened, enumerating every geometric instance described in the hierarchy. Flattening of the hierarchy typically results in several orders of magnitude increase in the size of data storage required to represent the pattern.

Since flattening the hierarchy results in such a large increase in the size of the file representing a given IC design, it is desirable to flatten the hierarchy at the latest point in the manufacture of a mask, which, in the best case, is at the time the mask design is loaded into the EB machine prior to physical manufacture. Currently however, this flattening process takes place at an earlier stage in the production of masks for some complicated IC's. This is because the original mask design for a complicated IC is typically manipulated after the original design is completed in order to perform one of a number of operations on the design. These operations are performed because of the precision needed in the masks for complicated IC's as the critical dimensions of these IC's approach the resolution limits of optical lithography. Currently, these operations require some sort of flattening of the original design data in order to be performed -- resulting in an earlier than desired flattening of the design data.

These operations include the performance of logical operations, the generation of optical proximity corrections, the generation of phase shifting masks, and the design rule checking of masks that have undergone these operations. For instance, since the physical mask making process may introduce known distortions in the mask that are dependent upon the particular EB machine being used, mask makers may use logical operations such as AND or

NOT operations between design layers to generate new mask layers which compensate for these known distortions. Further, mask designers may generate sub-resolution optical proximity correction features for a mask to compensate for the proximity effects which occur when very closely spaced pattern features are lithographically transferred to a resist layer on a wafer. Similarly, mask designers may generate phase shifting masks to overcome the effect of resolution limits on achievable circuit critical dimensions. Currently, each of these operations requires a flattening of the original design data in order to be performed. Further, and more importantly, because they do not maintain the original true hierarchical data format of the mask design, it is extremely difficult and time consuming to verify currently known masks upon which one of the previously mentioned operations has been performed using conventional verification tools which require the same hierarchical data format as the original mask.

Therefore, what is desired is a method and apparatus for performing operations on integrated circuit mask designs that solve the aforementioned problems of currently existing systems.

3. A Summary of the Invention

As discussed above, currently known systems for performing operations on integrated circuit design layouts are not capable of preserving the original hierarchy of the design. This leads to several problems including a large increase in data, a reduction in processing speed, and the loss of the ability to quickly check processed designs for correctness using conventional verification tools.

Accordingly, the present invention solves the aforementioned problems by providing a method and apparatus for performing an operation in accordance with a particular set of operating criteria on a hierarchically described integrated circuit layout such that the original hierarchy of the layout is maintained.

Thus in one embodiment of the present invention, in a system for performing an operation on a hierarchically described photolithography mask containing a plurality of cells, a computer program product is provided which includes a first program data. The first program data includes hierarchically configured correction data corresponding to the hierarchically described layout such that if the first program data were applied to the flattened layout an output comprising data representative of the result of performing the operation on the layout would be generated.

In one embodiment, the first program data is further characterized in that it comprises a plurality of delta planes that correspond to the plurality of cells. In this instance, the delta plane of a particular cell comprises data representative of the difference between a correction plane of the particular cell and the delta planes corresponding to the children cells of the particular cell. Further, the correction plane for each cell of the plurality of cells comprises data that would generate an output representative of the result of performing the operation on the cell if the correction plane were applied to the flattened cell data.

In one embodiment, the delta plane for each cell in the hierarchically described integrated circuit layout accounts for interaction between each of the cell's child cells and interaction between the cell's primitive geometry and each

of the cell's child cells.

In a further characterization of the above embodiment the first program data may comprise a set of arithmetically or logically described delta planes. Still further, the first program data may be described by a GDS-II data file.

5 The present invention as summarized above with respect to a first program data may be alternatively characterized as a method of performing an operation on a hierarchically described integrated circuit layout. The method includes, in one embodiment, providing a hierarchically described layout as a first input wherein the layout comprises a plurality of cells, and providing a
10 particular set of operating criteria as a second input. The method also includes performing a layout operation in accordance with the particular set of operating criteria on the layout and generating a first program data comprising hierarchically configured correction data corresponding to the hierarchically described layout. The first program data is generated in response to the layout
15 operation such that if the first program data were applied to the flattened layout an output comprising data representative of the result of performing the operation on the layout would be generated.

 In another embodiment of the method, the first program data comprises a plurality of delta planes that correspond to the plurality of cells. In this
20 embodiment, the delta plane of a particular cell comprises data representative of the difference between a correction plane of the particular cell and the delta planes corresponding to the children cells of the particular cell. Further, the correction plane for each cell of the plurality of cells comprises data that would generate an output representative of the result of performing the operation on
25 the cell if the correction plane were applied to the flattened cell data. Still further, in one embodiment, the delta plane for each cell in the hierarchically described integrated circuit layout accounts for interaction between each of the cell's child cells and interaction between the cell's primitive geometry and each of the cell's child cells.

In another embodiment wherein the first program data is characterized as comprising a plurality of delta planes corresponding to the plurality of cells, the step of generating the first program data further comprises compiling and linking the hierarchically described layout. In this instance, compiling
5 comprises generating a first correction layer for each cell in response to the particular set of operating criteria. Linking comprises modifying the correction layer of each cell in response to the particular set of operating criteria to generate the delta plane for each cell. In this instance, the delta plane of each cell accounts for interaction between each of the cell's child cells and interaction
10 between the cell's primitive geometry and each of the cell's child cells.

In a further characterization of this embodiment, for each cell in the layout the sum of the cell's delta plane and the delta planes of the cell's child cells comprises a correction plane of the cell. The correction plane for each cell in the plurality of cells comprises data that would generate an output data
15 representative of the result of performing the operation on the cell if the correction plane were applied to the flattened cell data. In a further instance of the above embodiment, compiling and linking each comprise a depth-wise traversing of the integrated circuit layout.

In another embodiment of the method, linking and compiling may
20 further comprise determining whether each cell has been previously defined and generating a first correction layer and delta plane comprising data indicative of a location of a first instance of a cell definition for each cell which has been previously defined.

A still further embodiment of the method includes combining the first
25 program data with the data describing the integrated circuit layout to produce a second program data that describes a first corrected layout. The second program data is then provided to a design rule checker apparatus, and the design rule checker apparatus is operated to determine whether the first corrected layout falls within a set of integrated circuit design rules.

30 Another embodiment of the invention is characterized as a

photolithography mask produced in accordance with the method steps summarized above.

5 Lastly, the method steps of the above embodiments may in one instance be performed by a computer running a program of instructions which implements these steps wherein the program is stored on any appropriate computer storage media such as a hard disk or server.

10 The present invention as summarized above with respect to a first program data and a method may also be alternatively characterized as an apparatus for performing an operation on a hierarchically described integrated circuit layout. The apparatus includes, in one embodiment, a resource for receiving hierarchically described layout as a first input wherein the layout comprises a plurality of cells, and a resource for receiving a particular set of operating criteria as a second input. The apparatus also includes an operation engine which performs a layout operation in accordance with the particular set of operating criteria on the hierarchically described layout, and a hierarchy preserver which generates a first program data comprising hierarchically configured correction data corresponding to the hierarchically described layout. The first program data is generated in response to the layout operation such that if the first program data were applied to the flattened layout an output comprising data representative of the result of performing the mask operation on the layout would be generated.

20 In another embodiment of the apparatus, the first program data comprises a plurality of delta planes that correspond to the plurality of cells. In this embodiment, the delta plane of a particular cell comprises data representative of the difference between a correction plane of the particular cell and the delta planes corresponding to the children cells of the particular cell. Further, the correction plane for each cell of the plurality of cells comprises data that would generate an output representative of the result of performing the operation on the cell if the correction plane were applied to the flattened cell

data. Still further, in one embodiment, the delta plane for each cell in the hierarchically described integrated circuit layout accounts for interaction between each of the cell's child cells and interaction between the cell's primitive geometry and each of the cell's child cells.

5 In another instance, the apparatus may also include a compiler and a linker. The compiler generates a first correction layer for each cell in response to the particular set of operating criteria. The linker modifies the correction layer of each cell in response to the particular set of operating criteria to generate the delta plane for each cell. In this instance, the delta plane of each
10 cell accounts for interaction between each of the cell's child cells and interaction between the cell's primitive geometry and each of the cell's child cells.

 In a further characterization of this embodiment, for each cell in the layout the sum of the cell's delta plane and the delta planes of the cell's child cells comprises a correction plane of the cell. The correction plane for each cell
15 in the plurality of cells comprises data that would generate an output data representative of the result of performing the operation on the cell if the correction plane were applied to the flattened cell data. In a further instance of the above embodiment, the compiler and the linker each perform a depth-wise traversing of the integrated circuit layout to generate the correction planes and
20 delta planes respectively.

 A still further embodiment of the apparatus includes a resource for combining the first program data with the data describing the integrated circuit layout to produce a second program data that describes a first corrected layout. A design rule checker is provided give an indication as to whether the first
25 corrected layout falls within a set of integrated circuit design rules.

 In another embodiment of the apparatus, the compiler and the linker may operate to determine whether each cell has been previously defined and to generate a first correction layer and delta plane comprising data indicative of a location of a first instance of a cell definition for each cell which has been
30 previously defined.

Lastly, the apparatus of the above embodiments may in one instance be characterized as a computer program product comprising a computer readable medium having a computer readable program code embodied therein for causing a computer to perform an operation on a hierarchically described integrated circuit layout such that the original hierarchy of the layout is maintained.

Each of the aforementioned embodiments of the present invention can be further characterized further by the following additional descriptions. For instance, the data planes of the first program data may include either arithmetically or logically described data.

Still further, the operation performed on the layout may include any logical or arithmetic operation including for instance, OPC corrections and logical operations such as AND, NOT, OR, NOR and NAND.

Similarly, the first program data may be in any hierarchical data format such as GDS-II, and the computer readable media may include any suitable media for the storage of either data files or program files such as a hard disk drive or a server. Lastly, each of the above embodiments of the present invention may be applied to any layout including bright-field, dark-field, and phase shifting layouts.

Other aspects and advantages of the present invention can be seen upon review of the figures, the detailed description and the claims which follow.

4. A Brief Description of the Drawings

The figures illustrate the invention by way of example, and not limitation. Like references indicate similar elements.

5 Fig. 1 illustrates a simple integrated circuit design layout and a hierarchical tree representation of the layout.

Fig. 2 illustrates a system level depiction of one embodiment of the invention.

Fig. 3 illustrates a simple representation of a typical hierarchical data file that would be output from the system of Fig. 2.

10 Fig. 4 illustrates in flowchart form, a method of performing a logical or arithmetic operation on a hierarchical integrated circuit design in which the hierarchical structure of the design layout is maintained according to one embodiment of the invention.

15 Fig. 5 illustrates how the method of Fig. 4 would provide for a logical NOT operation on one of the parent cells of Fig. 1 according to one embodiment of the invention.

Fig. 6 illustrates how the method of Fig. 4 would generate the delta plane of one of the parent cells of Fig. 1 for a logical NOT operation according to one embodiment of the invention.

20 Fig. 7 illustrates examples of optical proximity corrections that can be made to design layouts.

Fig. 8 is a depiction of a system for providing OPC correction to a design layout in accordance with one embodiment of the invention.

25 Fig. 9 illustrates how one embodiment of the system of Fig. 8 would provide for OPC correction of the primitive geometries of one of the cells of Fig. 1.

Figs. 10(a)-(b) illustrate how the method of Fig. 4 would generate a correction layer for overlap areas within one of the parent cells of Fig. 1 for an OPC operation according to one embodiment of the invention.

30 Fig. 11 illustrates how the method of Fig. 4 would generate the delta

plane of one of the parent cells of Fig. 1 for an OPC operation according to one embodiment of the invention.

Fig. 12 illustrates a further method for providing OPC correction to an integrated circuit design layout using one embodiment of the present invention.

5 Fig. 13 illustrates an example screen snapshot of an input design layout from a computer system executing one embodiment of the invention to provide OPC correction of the input design layout.

10 Fig. 14 illustrates an example screen snapshot of the final output from a computer system executing one embodiment of the invention to provide OPC correction to the input design of Fig. 13.

Fig. 15 illustrates a zoomed in example screen snapshot of the final output of Fig. 14.

15 Fig. 16 illustrates an example screen snapshot of a -1 OPC correction layer from a computer system executing one embodiment of the invention to provide OPC correction.

Fig. 17 illustrates an example screen snapshot of a +1 OPC correction layer from a computer system executing one embodiment of the invention to provide OPC correction.

20 Fig. 18 illustrates an example screen snapshot of a -2 OPC correction layer from a computer system executing one embodiment of the invention to provide OPC correction.

Fig. 19 illustrates an example screen snapshot of an individual cell that has been OPC corrected by a computer system executing one embodiment of the invention.

25 Although many details have been included in the description and the figures, the invention is defined by the scope of the claims. Only limitations found in those claims apply to the invention.

5. The Detailed Description

As described above, in the manufacture of photolithography masks, it is advantageous to flatten the data representing the IC design at the latest point in the actual manufacture of the masks. However, this flattening takes place earlier than desired in some instances. This is because the original layout for a complicated IC is typically manipulated after the original design is completed in order to perform one of a number of operations on the design. These operations include the performance of logical operations, the generation of optical proximity corrections, the generation of phase shifting masks, and the design rule checking of masks that have undergone these operations. Currently, these operations require some sort of flattening of the original design data in order to be performed -- resulting in an earlier than desired flattening of the design data. This early flattening of data results in large increases in required data storage and a corresponding slow down in the performance of these operations. Further, because existing verification systems typically require the same input data hierarchies, operations which modify a design in a non-hierarchical manner make it difficult if not impossible to perform the important step of verifying these modified designs.

The present invention solves the above problems by providing for the performance of operations on an input hierarchical IC design such that the original true hierarchy of the design is maintained. Various embodiments of the invention include computer systems for verifying and correcting masks for use in integrated circuit manufacturing, and for performance of logical operations on design layouts. These embodiments receive hierarchical mask definition data defining the look of a particular mask. These embodiments then generate an output set of data. In one embodiment, this output data includes OPC corrected mask definitions. Other embodiments of the invention include actual masks generated using systems that perform OPC correction or mask verification techniques. Still other embodiments of the invention include computer readable media (e.g., hard disks, CDs, and other computer program storage tools) having

computer programs that implement the OPC correction or mask verification techniques.

Before turning to a description of the present invention with respect to the figures, an overview of one embodiment of the concept of the present invention is provided. Thus, one embodiment of the invention utilizes a hierarchy preserver to receive a hierarchical definition of a layout and to generate one or more additional data layers that hierarchically include correction information provided by an engine which performs the operation on the design layout. These additional layers are then stored such that they are associated with each node in the hierarchic definition of that layer.

The following definitions are used in this specification: A correction plane is associated with any node (cell) in the hierarchy such that, by applying the correction plane to the flattened node, the output is the corrected design for that node. A delta plane is essentially the difference between a node's correction plane and the sum of all its immediate children's delta planes. Thus, the correction plane of a cell is equal to the delta plane for that cell plus the delta planes of the immediate child cells of that cell. Since the leaf cells of the hierarchy have no child cells, the correction plane for any leaf cell is equal to the delta plane of that leaf cell. In this manner, in one instance of the invention, the correction plane for each cell need not be stored since the overall correction to the layout can be provided by only storing the delta plane for each cell in the hierarchy.

The basic idea behind one embodiment of the present invention is described in two stages which comprise compilation and linking. In the compilation stage, corrections are generated for all geometry primitives in the hierarchy in accordance with the operation to be performed on the design layout. At the link stage, extra corrections due to the optical overlap of a parent cell's child cells and the parent cell's primitive geometry will be made. Therefore, only the additional correction is stored.

A delta algorithm computes the delta/additional information by

considering only the children cell overlaps and the overlap between the parent's geometry and child cells. Only these areas are considered because only the overlaps would contribute to the additional correction change needed for the parent cell. The overlap area is not limited to purely geometry overlap, but also includes proximity overlap. By employing a more general definition, all proximity effects / corrections can be taken into account. The output of the delta algorithm for a cell will be now called its delta plane. The leaves of the hierarchical tree thus have delta planes equal to their correction planes.

At compile time, the correction planes for all leaves can be generated by providing the flattened data describing the geometry primitives for each leaf to an operation engine which performs the desired operation on the provided flattened data. At link time, if there is no subcell overlap, then the correction plane for this parent cell equals to the sum of its children's delta planes (and as described above there would be no additional delta plane information to be stored for this parent cell). If there is an overlap, the overlap area is flattened, and an intermediate correction plane for the flattened overlap area is generated. Subsequently, this intermediate correction area is used to subtract the sum of all correction planes of its children, and the difference is the delta plane which is stored hierarchically to correspond to the cell being linked.

The current GDS-II, and most other design database formats describing a full layout, include placing different mask and chip levels on separate layers. What is being introduced in various embodiments of the invention is a twist on the layer concept--that an arithmetic layer capable of both logical (e.g., XOR, AND) and arithmetic operations can be based upon. For instance, with respect to an OPC operation, a correction layer representing a particular OPC feature can be based on an arithmetic layer such that for example, "-1" means a negative serif, a "+1" means a positive serif, and "-2" means end-butting where the overlap is infinitesimal in one direction. During linking, all correction layers are arithmetically generated using an algorithm to compute the incremental or differential corrections throughout the structure. These delta

planes, or arithmetic layers, are exposed in the database format as distinct layers (e.g., +1, -1, -2, etc. mapping to layers 1, 2, and 3). This allows the final correction layer for a parent cell to equal to the parent cell's delta plane and the incremental sum of all the delta planes of the parent cell's children and grandchildren and great-grandchildren, and so on, from the leaves' compile-time correction layer.

Hierarchical data management is also possible in the generation of corrections in an alternate embodiment of the invention in which the delta algorithm or arithmetic layers discussed above are not used. In this alternate embodiment, instead of taking and storing the difference between the correction layers of a parent cell and its children cells, a logical operation can be used to compare the correction between the parent and its children, and the "logical" instead of "arithmetic" difference is then stored at the parent cell.

Thus, as summarized above, the present invention provides a method and apparatus for data hierarchy maintenance in a system for mask description. A detailed description of preferred embodiments of the present invention is now provided with respect to the figures in which Fig. 1 illustrates a simple integrated circuit design layout 100 and a hierarchical tree representation of the layout 110. The circuit layout 100 comprises a final cell A which comprises Parent Cells B, C, and D. Parent Cell C comprises identical cells G1, G2, G3, G4, G5, and G6. Parent Cell D comprises cell H and identical cells I1 and I2. Parent cell B comprises identical Parent Cells E1 and E2, and identical Parent cells F1 and F2. Parent Cell E1 comprises Leaf cells J1 and K1 which comprise the primitive geometric structures illustrated in Fig. 1. Parent Cell E2 comprises Leaf cells J2 and K2 which comprise the same primitive geometric structures as cells J1 and K1. Parent Cell F1 comprises Leaf cells L1 and M1 which comprise the primitive geometric structures illustrated in Fig. 1. Parent Cell F2 comprises Leaf cells L2 and M2 which comprise the same primitive geometric structures as cells J1 and K1. The hierarchical tree layout 110 illustrates the aforementioned cells in a tree format with the leaf cells at the

bottom of the tree and with the final cell A at the top of the tree. Each of the leaf cells is also sometimes referred to herein as a leaf node or a child cell, while each of the cells above the leaf nodes is sometimes referred to herein as a parent cell or simply a node. The integrated circuit design layout 100 of Fig. 1 is provided as a reference IC design with respect to which the embodiments of the present invention are described below. The simple IC illustrated in Fig. 1 is used for example only, as the embodiments of the invention described below are capable of being applied to any IC which is described in a hierarchical format.

Fig. 2 illustrates in block diagram form a system incorporating one embodiment of the present invention. The system described is one in which a logical or arithmetic operation can be performed on a hierarchically described input IC design such that the resultant modified IC design retains the original true hierarchy of the input design. The basic elements of one embodiment of the system comprise a hierarchy preserver 210 and an operation engine 240. The hierarchy preserver 210 comprises a compiler 220 and a linker 230.

The hierarchy preserver 210 of the system accepts hierarchical design data 205 which describes an integrated circuit design 200 as an input. The hierarchy preserver 210, in one embodiment, accepts hierarchical design data 205 in a GDS-II format. In other embodiments, the hierarchy preserver 210 accepts hierarchical design data 205 described in any hierarchical file format. The compiler 220 of the hierarchy preserver 210 acts in conjunction with the operation engine 240 to provide a correction data layer for the geometry primitives at each node of the design data 205. The generated correction data layers are representative of the changes to be made to the geometry primitives at each node in accordance with the operation being performed by the operation engine 240 as will be described more fully below. In one embodiment of the invention, the operation engine 240 performs a logical operation such as AND or NOT on the input design data 205. In another embodiment of the invention, the operation engine 240 performs optical proximity corrections on the input design data 205. In still another embodiment of the invention, the operation

engine 240 performs design rule checking of the input design data 205.

After the compiler 220 has generated a correction data layer for each node of the input design data 205, the linker 230 acts in conjunction with the operation engine 240 to generate a delta plane for each node of the design. The delta plane for each cell is generated such that it is equal to the difference between the correction data layer information for the particular cell and the sum of all the correction data layers of the particular cell's children cells. In one embodiment, the delta plane for each cell is generated by a delta algorithm processed by the linker 230 which computes the delta/additional information by only considering overlaps within each cell. In one embodiment, these overlaps consist of the overlaps between a cell's children cells and any overlaps between a parent cell's own primitive geometry and that of its children cells. In one embodiment, these overlap areas are not limited to purely geometry overlap, but also include proximity overlap. The process by which the linker 230 generates a delta plane for each node of the input design 205 will be described more fully below.

After the linker 230 has generated the delta planes, the hierarchy preserver 210 generates output data 250 which represents the input design 205 modified in accordance with the operation performed by the operation engine 240. where the output data 250 retains the original true hierarchy of the input design data 205. This output data 250 comprises the original unaltered hierarchical design data 205, and a hierarchical correction data file 260. The hierarchical correction data file 260 comprises the delta plane data for each node of the design data 205 such that when the design data 205 and the correction data 260 are combined a modified design is produced which represents the operation performed on the original design data 205 by the operation engine 240.

The hierarchical output data 250 can then be used for a number of purposes. First, it could be provided to the hierarchy preserver 210 on line 262 in order for a new logical or arithmetic operation to be performed on the output

data 250. Further, since it is in hierarchical form, it can be provided to a conventional design rule checker 270 which accepts hierarchical data, in order that the new modified output design can be checked to verify that it meets the design rules for the particular integrated circuit being designed. Still further, the output data 250 can be used in mask production 265 by combining the design data 205 with the correction data 260 to construct a final data layout 275, flattening this combined data layout 280, and providing this flattened data to an electron beam machine to generate the actual physical mask which embodies the modified design data 285.

The generation of correction data layers and delta planes for each of the nodes of the design data 205 will now be developed further. With reference to Fig. 1, one embodiment of the compiler 220 accesses the design data using a depth wise traverse in which each branch of the final parent cell is accessed in order, and in which each branch is accessed from its leaf nodes upwards. Thus referring to Fig. 1, this embodiment of the compiler 220 would access the nodes of the integrated circuit layout 100 in the following order: J1, K1, E1, L1, M1, F1, L2, M2, F2, J2, K2, E2, B, G1, G2, G3, G4, G5, G6, C, H, I1, I2, D, and A. As the compiler 220 traverses the tree it provides the flattened data corresponding to the primitive geometry of each cell to the operation engine 240. The operation engine 240 performs an operation on the flattened data and returns the results of this operation to the hierarchy preserver 210. For instance, with respect to Fig. 1, if leaf cell J1 were compiled, the operation engine 240 would return flattened data $J' = J + \Delta J$. In one embodiment, the amount of data storage is decreased by the hierarchy preserver 210 which solves the aforementioned equation for ΔJ , and stores the value of ΔJ as the correction layer for cell J. This process is repeated for every cell in the design until the entire tree is traversed. The design data 205 is then linked by the linker 230 in the following manner. The tree is again traversed in the manner described above, and for each cell the overlap area is found and flattened. The flattened overlap area is then input to the operation engine 240 which in turn operates on

the data and returns it to the hierarchy preserver 210. The linker 230 utilizes the return data from the operation engine 240 to produce an intermediate correction layer which is used by the linker 230 to generate a delta plane for each cell. The generation of the delta plane will be more fully described below with respect to Figs. 6 and 10. The delta plane for each cell of the design is then stored in a hierarchical format corresponding to that of the input design data 205 in hierarchical correction data file 260.

In one embodiment of the invention as described in Fig. 2, the hierarchy preserver 210 may comprise a computer system executing program code stored on computer readable media that performs the functions of the compiler 220 and the linker 230. In one embodiment of the invention the operation engine 240 may also comprise a computer system executing program code stored on computer readable media. In one embodiment of the invention the hierarchy preserver 210 and the operation engine 240 comprise a single computer system executing a program code stored on computer readable media which performs the functions of the compiler 220, linker 230, and operation engine 240 together. In another embodiment, the hierarchy preserver 210 and the operation engine 240 comprise either a single computer system executing two or more different program codes or multiple separate computer systems executing two or more different program codes, one code for the functions of the hierarchy preserver 210, and a separate code for the functions of the operation engine 240. In this embodiment, the hierarchy preserver 210 may selectively provide data to the operation engine 240 through an API. With this embodiment, the hierarchy preserver 210 of the present invention can be modified to communicate and operate with currently existing operation engines 240 to provide the advantages of hierarchical data output.

The computer readable media referred to above may comprise any computer storage tools including but not limited to hard disks, CDs, floppy disks, and server memory. The computer systems executing the program code may, in the case of both the operation engine 240 and the hierarchy preserver

210. comprise any suitable computer system including a desktop computer running a Windows NT operating system or a Sun Solaris workstation for instance.

Turning to Fig. 3, a simplified representation of a typical hierarchical data file that would be output from one embodiment of the system of Fig. 2 is illustrated. Hierarchical data file of correction data 320 represents a simplified version of the correction data that would be generated if the system of Fig. 2 were applied to operate on the simplified integrated circuit layout 100 of Fig. 1. As described above, hierarchical design data 205 is provided to hierarchy preserver 210 which operates in conjunction with operation engine 240 to provide hierarchical correction data 260. A simplified hierarchical data file of the design layout 310 is shown to illustrate the minimal effect the present invention has on the increase in data upon the performance of an operation. For, as shown, the hierarchical data file of correction data 320 is able to be stored in a structure which corresponds one to one with the input data file 310. This facilitates quick combination of the two data files 310 and 320 in order to perform other functions on the overall modified design such as mask production and design rule checking.

Note also that when a cell is traversed by the hierarchy preserver 210, the hierarchy preserver 210 determines whether or not that cell is identical to a cell that has already been traversed. If this is the case, then the hierarchy preserver does not take the processing time to directly determine a delta plane for that cell. Instead, the hierarchy preserver maintains the true hierarchy by providing a pointer to that cell's first instance of being defined. For instance, this is illustrated by the hierarchical data file of correction data 320 by cells F1 and F2 which are identical cell's as shown in Fig. 1. As described earlier, in one embodiment of the invention, the hierarchy preserver 210 traverses the design data 205 in a depth wise manner from the leaf nodes to the final parent cell. In this manner, F1 would be traversed before F2, and thus correction data $\Delta F1$ would be generated and stored for this cell as indicated in file 320 by label 325.

When cell F2 is traversed however, only a pointer to the correction data for F1 is stored and no direct correction data is processed for F2. This is indicated by label 330. In this manner, both processing time and data volume are decreased.

Fig. 4 illustrates in flowchart form, a method of performing a logical or arithmetic operation on a hierarchical integrated circuit design in which the hierarchical structure of the design layout is maintained according to one embodiment of the invention. At its simplest level the method comprises a compiling process followed by a linking process. A hierarchical design data layout is provided at block 400 and the design tree is accessed at block 410 in the manner previously described with respect to Figs. 2 and 3. The compile process begins at block 415 wherein the hierarchical data for the first cell in the tree is obtained. Next, at block 425 it is determined whether or not the cell has been previously defined. If it has been previously defined, the obtained cell is associated with the previously defined correction data at block 427, and the next cell in the tree is obtained at block 415. If the cell has not been previously defined, the flattened primitive structure data of the cell is obtained at block 430 and provided to block 435 where an arithmetic or logical operation is performed on the flattened primitive data. The modified flattened primitive data is then provided to block 440, and this data is then processed at block 445 to separate the desired correction data as described earlier with respect to ΔJ of Fig. 2. The separated correction data is then stored in a hierarchical fashion corresponding to the original design data at block 450. At block 455, it is determined whether all of the cells have been traversed. If they have, the linking process begins at block 460, if not the compiling process continues at block 415 until such time when all the cells have been traversed and compiled.

The linking process begins in the same manner as the compile process with the accessing of the design tree at block 460. The process continues at block 465 wherein the hierarchical data for the first cell in the tree is obtained. Next, at block 470 it is determined whether or not the cell has been previously defined. If it has been previously defined, the obtained cell is associated with

the previously defined correction data at block 427, and the next cell in the tree is obtained at block 465. If the cell has not been previously defined, the overlaps of the cell are determined at block 475 as discussed earlier with respect to Fig. 2. These overlap areas are then flattened at block 480 and the flattened data is provided to block 435 where the arithmetic or logical operation is performed on the flattened data as discussed previously. This operated upon flattened data is then used to generate an intermediate correction layer at block 483, and at block 485 a delta plane for the cell is generated which is then stored in a hierarchical data format at block 490. The delta plane is the only data which needs to be kept for each cell in the tree. For, as discussed above, given a parent cell and its child cells, the difference between the correction information for the parent cell and the sum of all of its children's correction data is equal to the delta plane. Thus, it follows then that the leaves of the hierarchical tree have delta planes equal to their correction planes determined at compilation. At block 495 it is determined whether or not all the cells in the tree have been traversed. If so, then the process is stopped, and the output data may then be used for a variety of functions as discussed previously -- if not then the linking process continues at block 465 until all of the tree's cells have been traversed.

Fig. 5 illustrates how a specific embodiment of the present invention would perform a logical operation upon Parent cell F1 of Fig.1. In this instance, suppose what was desired was to perform a logical NOT operation on Parent cell F1. The desired output is illustrated in Fig. 5 as F1(NOT). To perform this operation directly would entail performing a NOT operation on the flattened data representing Leaf L1 and a NOT operation on the flattened data representing M1 using the operation engine 240 of Fig. 2 in the manner described above with respect to block 435 of Fig. 4. The results of these operations could then be stored in a hierarchical manner such that the correction data is associated with the appropriate nodes. These results are illustrated in Fig. 5 as L1(NOT) and M1(NOT). Without the teachings of the present invention however, one can not obtain the desired F1(NOT) results simply by

summing L1(NOT) and M1(NOT). This is illustrated by incorrect result 510 which is obtained by summing L1(NOT) and M1(NOT).

One embodiment of the present invention would operate to obtain the correct result F1(NOT) as follows. With reference to Fig. 2, the hierarchical design data 205, which in this simple example consists of the data representing Parent cell F1, is provided to the compiler 220 of hierarchy preserver 210. The compiler 220 provides the flattened data representing leaf L1 to the operation engine 240 which in this case performs a logical NOT operation on the supplied data and returns flattened data representative of the NOT of leaf L1. As described above, the compiler 220 then generates the correction data for L1 and stores this data in hierarchical correction data file 260. The same process is then repeated for leaf M1. As there is no primitive geometry associated with Parent cell F1, compilation of Parent F1 results in the generation of no correction data for F1. After the compilation of F1, the linker 230 operates to generate a delta plane 520 for Parent cell F1 during the linking stage as described more fully below with respect to Fig. 6. The delta plane 520 is generated such that, when summed with L1(NOT) and M1(NOT), the correct desired result F1(NOT) is obtained as shown in Fig. 5. This delta plane data is then stored hierarchically in hierarchical correction data file 260 such that it is associated with parent cell F1. This example is solely for illustration of the use of one embodiment of the present invention in the performance of a particular logical operation on a sample IC layout. As such, it is clear that this embodiment of the present invention could be used to perform any logical operation on any IC layout described in a hierarchical manner.

Fig. 6 illustrates heuristically how the delta plane 520 of Fig. 5 would be generated according to one embodiment of the present invention. With reference back to Fig. 2, after the operation engine 240 has performed a logical NOT operation on the flattened primitive data of leaf cells L1 and M1 respectively during the compile stage, the hierarchy preserver 210 operates during linking of Parent F1 to find the overlap areas within the parent cell and

flatten these areas 600, which generates overlap area 640. This flattened data for overlap area 640 is then provided to operation engine 240 at block 610, and the NOT of the overlap 650 is generated by the operation engine 240. The logical NOT operation is then performed on the parent F1 to generate F1(NOT) in a flattened form at block 620. Lastly, the delta plane 520 is generated by taking the difference between the NOT of the overlap area 650 and flattened F1(NOT), and storing this delta data in hierarchical correction data file 260.

The use of the present invention in a system for generating OPC corrected layouts is now described. As stated previously, as the features of integrated circuit designs have become smaller and smaller, the resolution limits of optical lithography have had an increased effect on the exposure process. For instance, it has been observed that differences in pattern development of circuit features depend upon the proximity of the features to one another. Proximity effects occur when very closely spaced pattern features are lithographically transferred to a resist layer on a wafer. The light waves of the closely spaced features interact and, as a result, distort the final transferred pattern features. Another problem that occurs when feature sizes and spacing approach the resolution limit of the lithographic tool is that corners (concave and convex) tend to overexpose or underexpose due to a concentration or scarcity of energy at each of the corners. Other types of problems, such as over- or under-exposure of small features when large and small features are transferred from the same mask pattern, also occur.

Numerous methods have been developed to overcome the proximity effect problem. These methods include: precompensating mask line widths, varying photoresist layer thicknesses, using multi-layer photoresist processes, using electron beam imaging in conjunction with optical imaging, and finally, adding additional features to the original mask pattern to compensate for proximity effects. This last method is known as Optical Proximity Correction (OPC).

Fig. 7 illustrates examples of optical proximity corrections that can be

made to design layouts. The additional features that are added to the original mask when OPC is utilized are typically sub-lithographic (i.e. have dimensions less than the resolution of the exposure tool) and thus do not transfer to the resist layer. Instead, they interact with the original pattern so as to improve the final transferred pattern and compensate for proximity effects. For instance, as shown in Figure 7, a desired pattern 710 may appear as actual pattern 720 when lithographically transferred without compensation for proximity effects. Using OPC techniques, positive serifs 732 and negative serifs 734 may be added to the desired pattern 710 to form the mask 730 needed to compensate for proximity effects. Similarly, in Figure 7, the effects of proximity distortions on a typical desired transistor gate pattern 740 are shown by actual transferred pattern 750 and 752. When OPC corrections represented by hammerheads 762, assist bars 764 and bias bars 766 are added to the original desired mask pattern, the original desired shape will be more accurately transferred. In the case of transistor gates, the hammerhead shapes 762 are designed to eliminate the effect of line end shortening to ensure that the polysilicon portion of the gate extends beyond the active region 742. The assist bars 764 are designed to compensate for the isolated gate effect which tends to decrease the width of the transferred gate pattern. Finally, the bias bars 766 are designed to eliminate the effect of densely packed gates which is shown by the additional transferred pattern 752. In some instances, currently existing OPC products utilize a rule-based algorithm to generate proximity corrections for a given geometry. In this type of system, the design layout is analyzed for predetermined layout patterns and one of the aforementioned types of OPC features are generated for that area of the design layout. However, unlike one embodiment of the present invention, previous OPC products are not capable of retaining the true hierarchical data structure of the original design layout.

An embodiment of the present invention which is capable of providing for the generation of OPC corrections for an IC design layout while retaining the true hierarchical data structure of the original design layout is described below

with respect to Fig. 8. This description includes by reference the above discussions of Figs. 2 and 4, as the system of Fig. 8 is a specific embodiment of the system and method described in these Figs. respectively.

Referring to Fig. 8, an integrated circuit chip design 800 is represented
5 by hierarchical design data 810, which in one embodiment is in a GDS-II data format. The design data 810 is provided as an input to a computer system running an OPC algorithm 840 which incorporates one embodiment of the present invention. The computer system 840 operates to produce hierarchical
10 correction data 845 in the manner described previously with respect to Figs. 2 and 4. In this respect, it can be seen that the computer system 840 comprises both the hierarchy preserver 210 and the operation engine 240 of Fig. 2, where the operation engine 240 of computer system 840 is a specifically defined OPC operation engine 240 that operates on the input design data 810 to provide for optical proximity corrections.

15 As shown in Fig. 8, the output hierarchical correction data 845 can be provided to a conventional design rule checker 850 along with the original design data 810 to design rule check the OPC corrected design. Similarly, the output could be used in the production of a lithography mask by combining the design data 810 with the correction data 845 as shown at block 860. This
20 combined data can then be flattened and written to an EB machine as shown at block 865 in order for the EB machine to operate to produce the mask 870.

In one embodiment of the system of Fig. 8, the computer system 840 executes a computer program code stored on computer readable media that performs the functions of the compiler 220, the linker 230, and the OPC
25 operation engine 240. In another embodiment, the computer system 840 comprises either a single computer system executing two or more different program codes or multiple separate computer systems executing two or more different program codes, one program code for the functions of the hierarchy preserver 210, and a separate program code for the functions of the OPC
30 operation engine 240. In this embodiment, the hierarchy preserver 210 may

selectively provide data to the OPC operation engine 240 through an API. With this embodiment, the hierarchy preserver 210 of the present invention can be modified to communicate and operate with currently existing OPC operation engines 240 to provide the advantages of hierarchical data output.

5 The computer readable media referred to above may comprise any computer storage tools including but not limited to hard disks, CDs, floppy disks, and server memory. The computer systems executing the program code may, in the case of both the OPC operation engine 240 and the hierarchy preserver 210, comprise any suitable computer system including a desktop
10 computer running a Windows NT operating system or a Sun Solaris workstation for instance.

 Operation engines which simply provide for OPC correction given a hierarchical input are well known in the field. In one embodiment of the system of Fig. 8, the OPC engine 240 is a rule-based OPC engine capable of generating
15 OPC features in a manner that is controllable by the user of the system. For instance, the user can define the correction rules to be applied, and the size of the features to be applied to the design layout. Further, in one embodiment of the system, the location and size of bias lines 766 can be dependent upon the size and pitch of the IC pattern features being corrected, and/or restricted to
20 being used only in critical areas of the design such as transistor gate regions. Still further, in another embodiment of the system the OPC engine 240 is capable of applying assist features 764 either in a localized manner to critical areas such as transistor gates or to the entire IC design globally. Still further, in
25 another embodiment, the OPC engine can selectively place correction features in critical areas while not placing those correction features in areas that do not require them for accurate circuit performance. In one instance of this embodiment, the OPC engine can restrict the placing of biasing and assist features to transistor gates, while leaving the non-critical interconnect regions of the polysilicon gate layer uncorrected. In another instance, the OPC engine
30 distinguishes critical transistor gate line-ends and applies hammerhead

corrections to these areas to alleviate line-end shortening. Lastly, in another embodiment of the invention, the OPC operation engine is capable of providing for OPC correction of Phase Shifting Masks such as those disclosed in the United States patent application entitled, "Phase Shifting Circuit Manufacture Method and Apparatus" having serial number 08/931,921, filed September 17, 1997, and invented by Fang-Cheng Chang, Yao-Ting Wang and Yagyensh C. Pati which was previously incorporated by reference herein.

Fig. 9 illustrates how one embodiment of the system of Fig. 8 provides for OPC correction of the primitive geometries of leaf cells J1 and K1 of Fig. 1. Shown are uncorrected leaf cells J1 and K1 of Parent cell E1. The flattened primitive geometry data of J1 is provided to the hierarchy preserver 210, and the compiler 220 operates with the OPC engine 240 to provide a correction plane $\Delta J1$ in the manner discussed previously with respect to Fig. 2. In this case, the OPC engine has decided based on its rule definitions that the primitive geometry of J1 requires positive serifs 905 in order to provide the proper result when the mask is produced and used to expose a wafer. The same process is performed on the flattened primitive geometry of K1 to generate correction plane $\Delta K1$, again comprising positive serifs 905. Each of these cells is then linked by the linker 230 as discussed previously to generate delta planes for each cell. Since these cells are leaf nodes and have no overlap areas, their respective delta planes are equal to their compiled correction planes. Also illustrated are corrected leaf cells 910 and 920 which represent $J1 + \Delta J1$, and $K1 + \Delta K1$ respectively.

Figs. 10(a)-(b) illustrate how the method of Fig. 4 would generate an intermediate correction layer for overlap areas within Parent cell E1 of Fig. 1 for an OPC operation according to one embodiment of the invention. Fig. 10(b) illustrates the overlap area 1000 between corrected leaf cell J1 910 and the corrected leaf cell K1 920. As discussed above with respect to Figs. 2 and 4, during the linking process for cell E1, this overlap area is determined and the data corresponding to this area is flattened. The flattened overlap area is then provided to the OPC operation engine 240 which operates on the data to provide

an intermediate correction plane 1020. Note that in the case described here where the primitive structures overlap a discrete amount, negative serifs 1010 are provided for the intermediate correction plane. In the situation described below with respect to Fig. 10(b), an alternate parent E1 is illustrated in which the corrected leaf cells K1 and K2 shown as 910b and 920b respectively. This situation illustrates an infinitesimal overlap between the two corrected primitive geometries. In one embodiment of the invention, an intermediate correction plane 1020b is provided for these infinitesimal overlap situations such that a -2 layer is provided to compensate for end butting effects.

Fig. 11 illustrates how the method of Fig. 4 would generate the delta plane of parent cell E1 of Fig. 1 for an OPC operation according to one embodiment of the invention. As described by block 1100, at the link stage for cell E1, the overlap areas within E1 are determined and the area data is flattened. This is illustrated as overlap area 1000. Next, as described by block 1110, an intermediate correction plane 1020 for this overlap area 1000 is generated as described above with respect to Fig. 10(a). At block 1120, the correction planes 910 and 920 of all the children cells of E1 are summed to generate summed children correction data 1140. The last step as described by block 1130 is to generate the delta plane 1150 for cell E1 and store this data hierarchically. This is accomplished in one embodiment by subtracting the summed children correction data 1140 from the intermediate correction plane 1020 to obtain the delta plane 1150. Also illustrated in Fig. 11 is the final correction plane 1160 for cell E1 which as defined earlier represents the total of the corrections needed to be applied to the cell's design data in order to properly apply the particular operation, which here is OPC, to the cell. The correction plane 1160 comprises the E1's delta plane summed with the correction planes 910 and 920 of its children J1 and K1 respectively.

Fig. 12 illustrates a further method for providing OPC correction to a design layout using one embodiment of the present invention. At block 1200 an integrated circuit design layout is first provided. The hierarchically formatted

design data corresponding to this design layout is then provided to a system which performs a rule based OPC correction on the design data in accordance with the system of Fig. 8 as shown at block 1205. The system of Fig. 8 generates an output of hierarchical correction data as described above, and this
5 correction data is combined with the original design data to generate a hierarchically described rule-based OPC corrected design data as shown at block 1210. Using this corrected design data a simulated image of the mask which this corrected design data would produce is generated at block 1215. This simulation can be generated utilizing a Hopkins equation based simulation
10 device such as that described generally in the United States provisional patent application entitled, "Mask Verification, Correction, and Design Rule Checking" having serial number 60/059,306, filed September 17, 1997, and invented by Fang-Cheng Chang, Yao-Ting Wang and Yagyensh C. Pati, United States patent application entitled, "Mask Verification, Correction, and Design
15 Rule Checking", filed September 16, 1998, and invented by Fang-Cheng Chang, Yao-Ting Wang and Yagyensh C. Pati, and also more specifically in the United States patent application entitled "Visual Inspection and Verification System", filed August 7, 1998, and invented by Fang-Cheng Chang, Yao-Ting Wang, Yagyensh C. Pati, and Linard Karklin, each of which were previously
20 incorporated by reference herein.

The simulated image of the corrected mask is then compared to the desired design image at block 1220 to determine whether or not the initial rule based OPC correction was sufficient to correct the design to within a set of user defined design parameters as shown at block 1225. Methods for performing this
25 comparison are disclosed in the aforementioned United States provisional patent application entitled, "Mask Verification, Correction, and Design Rule Checking." If the result of the comparison is that the design parameters have been achieved, the corrected design data can then be input to a design rule checker which analyzes the corrected design for any violations of the established
30 design rules for the particular integrated circuit design as shown at block 1235.

If the corrected design is within design rules, the corrected design data can then be flattened and a mask can be produced using an EB machine as shown at block 1245. If the design rules have not been met, a decision must be made as to whether or not to redesign the mask as shown at block 1250.

5 If the decision is not to redesign, but to try and fix the problem by continuing with the iterative correction process, a model based OPC algorithm is then run on the corrected design. Similarly, if the original corrected design data did not meet the design parameters of block 1225, the original corrected design data is input to a model based OPC algorithm. The model based OPC
10 algorithm is then used to perform more detailed specific corrections to the original corrected design as shown at block 1230. The model based OPC corrected design can then be provided to block 1215 where a simulated image of the model based OPC corrected design is produced and once again compared to the desired image. Before entering the OPC corrected design into a
15 conventional design rule checker product for analysis of the design, the simulated image of the model based OPC corrected design must be manipulated into a format that is acceptable by a conventional design rule checker. One way of doing this is to generate a Manhattan geometry representation of the simulated image based on an edge checking technique as described more fully in
20 the aforementioned and incorporated United States provisional patent application entitled, "Mask Verification, Correction, and Design Rule Checking" and the United States utility patent application of the same name. This whole process can be continued until a corrected design is produced which meets both the user defined design parameters and the circuit specific design
25 rules.

 In one embodiment of this process, the model based OPC algorithm is capable of responding to user defined input. For instance, in one embodiment, the user can control the complexity level of the corrections he wants to be applied in order to control data volume and overall process speed. Similarly, in
30 another embodiment the user can control the size of correction features to be

applied by the model based algorithm. Still further, in another embodiment, the user can define the correction criteria to be applied by the algorithm.

The remaining Figs. 13-19 illustrate example screen snapshots from a computer system executing one embodiment of the present invention to provide OPC corrections for a hierarchical input IC design layout. For instance, Fig. 13 illustrates an example screen snapshot of the input design layout which is to be OPC corrected. The user interface 1300 of the design program comprises a design window 1330 in which is illustrated a portion of the IC design layout to be corrected. The design layout includes a diffusion layer 1390 and a layer of polysilicon structures such as primitive structures 1320. A cell 1310, similar to the sample parent cells E1 and F1 of Fig. 1, is also depicted in design window 1330.

Fig. 14 illustrates an example screen snapshot of the final output from a computer system executing one embodiment of the invention to provide OPC correction to the input design of Fig. 13. The design window 1330 of user interface 1300 shows a cell 1310 comprising primitive structures 1320 which have been OPC corrected. The cell 1310 comprises OPC features such as hammerheads 1410, assist lines 1420, bias lines 1430, positive serifs 1440, and negative serifs 1450. The output depicted in Fig. 14 is representative of all of the corrections which would have to be made to compensate for all OPC effects on the entire design. Thus, these corrections represent the final linked output of this embodiment of the present invention in which all overlaps between cells in the hierarchy have been resolved and compensated for. The OPC features depicted in Fig. 14 are shown in greater detail in Fig. 15 which is a zoomed in example screen snapshot of Fig. 14.

Fig. 16 illustrates an example screen snapshot of a -1 OPC correction layer from a computer system executing one embodiment of the invention to provide OPC correction. This layer contains corrections to cell 1310 including assist lines 1420, bias lines 1430, and negative serifs 1450.

Fig. 17 illustrates an example screen snapshot of a +1 OPC correction

layer from a computer system executing one embodiment of the invention to provide OPC correction. This layer contains corrections to cell 1310 including hammerheads 1410, assist lines 1420, and positive serifs 1440.

5 Fig. 18 illustrates an example screen snapshot of a -2 OPC correction layer from a computer system executing one embodiment of the invention to provide OPC correction. This layer contains corrections to cell 1310 including end butting correction feature 1810.

10 Fig. 19 illustrates an example screen snapshot of an individual cell 1310 that has been OPC corrected by a computer system executing one embodiment of the invention. The design window 1330 illustrates a cell 1310 to which its linked correction layer has been applied. The corrections applied to the cell 1310 include hammerheads 1410, assist lines 1420, positive serifs 1440, and negative serifs 1450. Note that the corrections to cell 1310 are different than those illustrated in Fig. 14 because Fig. 14 is a representation of all the
15 corrections to the entire design -- while Fig. 19 only illustrates those corrections necessary to correct cell 1310 individually. In other words, the corrections illustrated in Fig. 19 do not take into account the interactions of cell 1310 with other cells adjacent to it. For instance, note that the bias lines 1430 of Fig. 14 are not present in Fig. 19.

20 Although illustrative embodiments of the invention have been described in detail herein with reference to the accompanying drawings, it is to be understood that the invention is not limited to those precise embodiments. They are not intended to be exhaustive or to limit the invention to the precise forms disclosed. As such, many modifications and variations will be apparent to
25 practitioners skilled in this art. Accordingly, it is intended that the scope of the invention be defined by the following claims and their equivalents.

6. The Claims

What is claimed is:

1. In a system for performing an operation in accordance with a particular set of operating criteria on a hierarchically described integrated circuit layout comprising a plurality of cells, a computer program product comprising computer readable media, the computer program product including first program data comprising hierarchically configured correction data corresponding to the hierarchically described layout, wherein if the first program data were applied to the flattened layout an output comprising data representative of the result of performing the operation on the layout would be generated.
2. The computer program product of claim 1, wherein the first program data comprises a plurality of delta planes corresponding to the plurality of cells, wherein the delta plane of a particular cell comprises data representative of the difference between a correction plane of the particular cell and the delta planes corresponding to the children cells of the particular cell.
3. The computer program product of claim 2, wherein the correction plane for each cell of the plurality of cells comprises data that would generate an output data representative of the result of performing the operation on the cell if the correction plane were applied to the flattened cell data.
4. The computer program product of claim 3 wherein the delta plane for each cell in the hierarchically described integrated circuit layout accounts for interaction between each of the cell's child cells and interaction between the cell's primitive geometry and each of the cell's child cells.

5. The computer program product of claim 2 wherein the first program data comprises a set of arithmetically described delta planes.

5 6. The computer program product of claim 2 wherein the first program data comprises a set of logically described delta planes.

7. The computer program product of claim 1, wherein the operation comprises one of a group of operations including logical and arithmetic operations.

10

8. The computer program product of claim 1, wherein the first program data comprises data described by a GDS-II data file.

15 9. The computer program product of claim 1 wherein the first program data comprises data which corrects the layout for optical proximity effects.

10. The computer program product of claim 1 wherein the first program data comprises data which corrects the layout for a logical operation performed on the layout.

20

11. The computer program product of claim 10 wherein the logical operation comprises one of a group of logical operations including AND, NOT, OR, NOR and NAND.

25

12. The computer program product of claim 1 wherein the layout comprises one of a bright field and a dark field layout.

13. The computer program product of claim 1 wherein the layout comprises a phase shifting layout.

30

14. . A method of performing an operation on a hierarchically described integrated circuit layout, the method comprising:

5 providing the hierarchically described integrated circuit layout as a first input wherein the layout comprises a plurality of cells;

providing a particular set of operating criteria as a second input;

performing a layout operation in accordance with the particular set of operating criteria on the layout; and

10 generating a first program data comprising hierarchically configured correction data corresponding to the hierarchically described layout in response to the layout operation such that if the first program data were applied to the flattened layout an output comprising data representative of the result of performing the operation on the layout would be generated.

15 15. The method of performing an operation on a hierarchically described integrated circuit layout of claim 14 wherein the first program data comprises a plurality of delta planes corresponding to the plurality of cells, wherein the delta plane of a particular cell comprises data representative of the difference between a correction plane of the particular cell and the delta planes
20 corresponding to the children cells of the particular cell.

16. The method of performing an operation on a hierarchically described integrated circuit layout of claim 15, wherein the correction plane for each cell in the plurality of cells comprises data that would generate an output
25 data representative of the result of performing the operation on the cell if the correction plane were applied to the flattened cell data.

17. The method of performing an operation on a hierarchically described integrated circuit layout of claim 16 wherein the delta plane for each
30 cell in the hierarchically described integrated circuit layout accounts for

interaction between each of the cell's child cells and interaction between the cell's primitive geometry and each of the cell's child cells.

18. The method of performing an operation on a hierarchically
5 described integrated circuit layout of claim 15 wherein the first program data comprises a set of arithmetically described delta planes.

19. The method of performing an operation on a hierarchically
described integrated circuit layout of claim 15 wherein the first program data
10 comprises a set of logically described delta planes.

20. The method of performing an operation on a hierarchically
described integrated circuit layout of claim 14 wherein the first program data
comprises a plurality of delta planes corresponding to the plurality of cells, and
15 wherein generating the first program data comprises:

compiling the hierarchically described layout, wherein compiling
comprises generating a first correction layer for each cell of the plurality of cells
in response to the particular set of operating criteria; and

linking the hierarchically described layout, wherein linking comprises
20 modifying the correction layer of each cell in response to the particular set of
operating criteria to generate the delta plane for each cell such that the delta
plane of each cell accounts for interaction between each of the cell's child cells
and interaction between the cell's primitive geometry and each of the cell's child
cells.

25

21. The method of performing an operation on a hierarchically
described integrated circuit layout of claim 20 wherein for each cell in the layout
the sum of the cell's delta plane and the delta planes of the cell's child cells
comprises a correction plane of the cell wherein the correction plane for each
30 cell in the plurality of cells comprises data that would generate an output data

representative of the result of performing the operation on the cell if the correction plane were applied to the flattened cell data.

5 22. The method of performing an operation on a hierarchically described integrated circuit layout of claim 20 wherein compiling comprises a depth-wise traversing of the layout.

10 23. The method of performing an operation on a hierarchically described integrated circuit layout of claim 20 wherein linking comprises a depth-wise traversing of the layout.

 24. The method of performing an operation on a hierarchically described integrated circuit layout of claim 14 further comprising:
 combining the first program data with the data describing the integrated
15 circuit layout to produce a second program data that describes a first corrected layout;
 providing the second program data to a design rule checker apparatus;
 and
 operating the design rule checker apparatus to determine whether the
20 first corrected layout falls within a set of integrated circuit design rules.

25 25. The method of performing an operation on a hierarchically described integrated circuit layout of claim 14 wherein the first program data is provided on a computer readable media.

 26. The method of performing an operation on a hierarchically described integrated circuit layout of claim 14 wherein the operation comprises one of a group of operations including logical and arithmetic operations.

30 27. The method of performing an operation on a hierarchically

described integrated circuit layout of claim 14 wherein the first program data comprises data described by a GDS-II data file.

5 28. The method of performing an operation on a hierarchically described integrated circuit layout of claim 14 wherein the first program data comprises data which corrects the layout for optical proximity effects.

10 29. The method of performing an operation on a hierarchically described integrated circuit layout of claim 14 wherein the first program data comprises data which corrects the layout for a logical operation performed on the layout.

15 30. The method of performing an operation on a hierarchically described integrated circuit layout of claim 29 wherein the logical operation comprises one of a group of logical operations including AND, NOT, OR, NOR and NAND.

20 31. The method of performing an operation on a hierarchically described integrated circuit layout of claim 14 wherein the layout comprises one of a bright field and a dark field layout.

25 32. The method of performing an operation on a hierarchically described integrated circuit layout of claim 14 wherein the layout comprises a phase shifting layout.

30 33. A program storage device readable by a machine, tangibly embodying a program of instructions executable by said machine to perform method steps to perform an operation on a hierarchically described integrated circuit layout, the method comprising:
 providing the hierarchically described integrated circuit layout as a first

input wherein the layout comprises a plurality of cells;
providing a particular set of operating criteria as a second input;
performing a layout operation in accordance with the particular set of
operating criteria on the layout; and

5 generating a first program data comprising hierarchically configured
correction data corresponding to the hierarchically described layout in response
to the layout operation such that if the first program data were applied to the
flattened layout an output comprising data representative of the result of
performing the operation on the layout would be generated.

10

34. The program storage device readable by a machine of claim 33
wherein the first program data comprises a plurality of delta planes
corresponding to the plurality of cells, wherein the delta plane of a particular
cell comprises data representative of the difference between a correction plane
15 of the particular cell and the delta planes corresponding to the children cells of
the particular cell.

35. The program storage device readable by a machine of claim 34,
wherein the correction plane for each cell in the plurality of cells comprises data
20 that would generate an output data representative of the result of performing the
operation on the cell if the correction plane were applied to the flattened cell
data.

36. The program storage device readable by a machine of claim 35
25 wherein the delta plane for each cell in the hierarchically described integrated
circuit layout accounts for interaction between each of the cell's child cells and
interaction between the cell's primitive geometry and each of the cell's child
cells.

30 37. The program storage device readable by a machine of claim 34

wherein the first program data comprises a set of arithmetically described delta planes.

5 38. The program storage device readable by a machine of claim 34 wherein the first program data comprises a set of logically described delta planes.

10 39. The program storage device readable by a machine of claim 33 wherein the first program data comprises a plurality of delta planes corresponding to the plurality of cells, and wherein generating the first program data comprises:

 compiling the hierarchically described layout, wherein compiling comprises generating a first correction layer for each cell of the plurality of cells in response to the particular set of operating criteria; and

15 linking the hierarchically described layout, wherein linking comprises modifying the correction layer of each cell in response to the particular set of operating criteria to generate the delta plane for each cell such that the delta plane of each cell accounts for interaction between each of the cell's child cells and interaction between the cell's primitive geometry and each of the cell's child cells.

20

 40. The program storage device readable by a machine of claim 39 wherein for each cell in the layout the sum of the cell's delta plane and the delta planes of the cell's child cells comprises a correction plane of the cell wherein

25 the correction plane for each cell in the plurality of cells comprises data that would generate an output data representative of the result of performing the operation on the cell if the correction plane were applied to the flattened cell data.

30 41. The program storage device readable by a machine of claim 39

wherein compiling comprises a depth-wise traversing of the layout.

42. The program storage device readable by a machine of claim 39 wherein linking comprises a depth-wise traversing of the layout.

5

43. The program storage device readable by a machine of claim 33 wherein the first program data is provided on a computer readable media.

10

44. The program storage device readable by a machine of claim 33 wherein the operation comprises one of a group of operations including logical and arithmetic operations.

15

45. The program storage device readable by a machine of claim 33 wherein the first program data comprises data described by a GDS-II data file.

46. The program storage device readable by a machine of claim 33 wherein the first program data comprises data which corrects the layout for optical proximity effects.

20

47. The program storage device readable by a machine of claim 33 wherein the first program data comprises data which corrects the layout for a logical operation performed on the layout.

25

48. The program storage device readable by a machine of claim 47 wherein the logical operation comprises one of a group of logical operations including AND, NOT, OR, NOR and NAND.

30

49. The program storage device readable by a machine of claim 33 wherein the layout comprises one of a bright field and a dark field layout.

50. The program storage device readable by a machine of claim 33 wherein the layout comprises a phase shifting layout.

5 51. The program storage device readable by a machine of claim 33 wherein the program storage device comprises a hard disk drive.

52. The program storage device readable by a machine of claim 33 wherein the program storage device comprises a server.

10 53. An apparatus for performing an operation on a hierarchically described integrated circuit layout, the apparatus comprising:

a resource for receiving the hierarchically described integrated circuit layout as a first input wherein the layout comprises a plurality of cells;

15 a resource for receiving a particular set of operating criteria as a second input;

an operation engine which performs a layout operation in accordance with the particular set of operating criteria on the hierarchically described layout; and

20 a hierarchy preserver which generates a first program data comprising hierarchically configured correction data corresponding to the hierarchically described layout in response to the layout operation such that if the first program data were applied to the flattened layout an output comprising data representative of the result of performing the operation on the layout would be generated.

25

54. The apparatus for performing an operation on a hierarchically described integrated circuit layout of claim 53 wherein the first program data comprises a plurality of delta planes corresponding to the plurality of cells, wherein the delta plane of a particular cell comprises data representative of the difference between a correction plane of the particular cell and the delta planes

30

corresponding to the children cells of the particular cell.

55. The apparatus for performing an operation on a hierarchically described integrated circuit layout of claim 54, wherein the correction plane for each cell in the plurality of cells comprises data that would generate an output data representative of the result of performing the operation on the cell if the correction plane were applied to the flattened cell data.

56. The apparatus for performing an operation on a hierarchically described integrated circuit layout of claim 55 wherein the delta plane for each cell in the hierarchically described integrated circuit layout accounts for interaction between each of the cell's child cells and interaction between the cell's primitive geometry and each of the cell's child cells.

57. The apparatus for performing an operation on a hierarchically described integrated circuit layout of claim 54 wherein the first program data comprises a set of arithmetically described delta planes.

58. The apparatus for performing an operation on a hierarchically described integrated circuit layout of claim 54 wherein the first program data comprises a set of logically described delta planes.

59. The apparatus for performing an operation on a hierarchically described integrated circuit layout of claim 53 wherein the first program data comprises a plurality of delta planes corresponding to the plurality of cells, and wherein the hierarchy preserver comprises:

a compiler which generates a first correction layer for each cell in response to the particular set of operating criteria; and

a linker which modifies the first correction layer of each cell in response to the particular set of operating criteria to generate the delta plane for each cell

such that the delta plane of each cell accounts for interaction between each of the cell's child cells and interaction between the cell's primitive geometry and each of the cell's child cells.

5 60. The apparatus for performing an operation on a hierarchically described integrated circuit layout of claim 59 wherein for each cell in the layout the sum of the cell's delta plane and the delta planes of the cell's child cells comprises a correction plane of the cell wherein the correction plane for each cell in the plurality of cells comprises data that would generate an output data
10 representative of the result of performing the operation on the cell if the correction plane were applied to the flattened cell data.

 61. The apparatus for performing an operation on a hierarchically described integrated circuit layout of claim 59 wherein the generation of the first
15 correction layers comprises a depth-wise traversing of the layout.

 62. The apparatus for performing an operation on a hierarchically described integrated circuit layout of claim 59 wherein the generation of the delta planes comprises a depth-wise traversing of the layout.
20

 63. The apparatus for performing an operation on a hierarchically described integrated circuit layout of claim 53 further comprising:
 a resource for combining the first program data with the data describing the integrated circuit layout to produce a second program data that describes a
25 first corrected layout; and
 a design rule checker apparatus which receives the second program data and which provides an output that indicates whether the first corrected layout falls within a set of integrated circuit design rules.

30 64. The apparatus for performing an operation on a hierarchically

described integrated circuit layout of claim 53 wherein the first program data is provided on a computer readable media.

5 65. The apparatus for performing an operation on a hierarchically described integrated circuit layout of claim 53 wherein the operation comprises one of a group of operations including logical and arithmetic operations.

10 66. The apparatus for performing an operation on a hierarchically described integrated circuit layout of claim 53 wherein the first program data comprises data described by a GDS-II data file.

15 67. The apparatus for performing an operation on a hierarchically described integrated circuit layout of claim 53 wherein the first program data comprises data which corrects the layout data for optical proximity effects.

20 68. The apparatus for performing an operation on a hierarchically described integrated circuit layout of claim 53 wherein the first program data comprises data which corrects the layout for a logical operation performed on the layout data.

25 69. The apparatus for performing an operation on a hierarchically described integrated circuit layout of claim 68 wherein the logical operation comprises one of a group of logical operations including AND, NOT, OR, NOR and NAND.

 70. The apparatus for performing an operation on a hierarchically described integrated circuit layout of claim 53 wherein the layout comprises one of a bright field and a dark field layout.

71. The apparatus for performing an operation on a hierarchically described integrated circuit layout of claim 53 wherein the layout comprises a phase shifting layout.

5 72. The apparatus for performing an operation on a hierarchically described integrated circuit layout of claim 53 wherein the apparatus comprises a computer program product which comprises a computer usable medium having a computer readable program code embodied therein for causing a
10 circuit layout.

73. A photolithography mask which has been produced according to a method for performing an operation on a hierarchically described integrated circuit layout, the method comprising:

15 providing the hierarchically described integrated circuit layout as a first input wherein the layout comprises a plurality of cells;

 providing a particular set of operating criteria as a second input;

 performing a layout operation in accordance with the particular set of operating criteria on the layout; and

20 generating a first program data comprising hierarchically configured correction data corresponding to the hierarchically described layout in response to the layout operation such that if the first program data were applied to the flattened layout an output comprising data representative of the result of performing the operation on the layout would be generated;

25 providing the first program data and data describing the layout to a mask making apparatus; and

 generating the photolithography mask with the mask making apparatus in response to the data describing the layout and the first program data.

74. The photolithography mask of claim 73, wherein the first
program data comprises a plurality of delta planes corresponding to the plurality
of cells, wherein the delta plane of a particular cell comprises data
representative of the difference between a correction plane of the particular cell
5 and the delta planes corresponding to the children cells of the particular cell.

75. The photolithography mask of claim 74, wherein the correction
plane for each cell in the plurality of cells comprises data that would generate an
output data representative of the result of performing the operation on the cell if
10 the correction plane were applied to the flattened cell data.

76. The photolithography mask of claim 75 wherein the delta plane
for each cell in the hierarchically described integrated circuit layout accounts for
interaction between each of the cell's child cells and interaction between the
15 cell's primitive geometry and each of the cell's child cells.

77. The photolithography mask of claim 74 wherein the first
program data comprises a set of arithmetically described delta planes.

78. The photolithography mask of claim 74 wherein the first program
20 data comprises a set of logically described delta planes.

79. The photolithography mask of claim 73 wherein the first program
data comprises a plurality of delta planes corresponding to the plurality of cells,
25 and wherein generating the first program data comprises:

compiling the hierarchically described layout, wherein compiling
comprises generating a first correction layer for each cell of the plurality of cells
in response to the particular set of operating criteria; and

linking the hierarchically described layout, wherein linking comprises
30 modifying the correction layer of each cell in response to the particular set of

operating criteria to generate the delta plane for each cell such that the delta plane of each cell accounts for interaction between each of the cell's child cells and interaction between the cell's primitive geometry and each of the cell's child cells.

5

80. The photolithography mask of claim 79 wherein for each cell in the layout the sum of the cell's delta plane and the delta planes of the cell's child cells comprises a correction plane of the cell wherein the correction plane for each cell in the plurality of cells comprises data that would generate an output data representative of the result of performing the operation on the cell if the correction plane were applied to the flattened cell data.

10

81. The photolithography mask of claim 79 wherein compiling comprises a depth-wise traversing of the layout.

15

82. The photolithography mask of claim 79 wherein linking comprises a depth-wise traversing of the layout.

20

83. The photolithography mask of claim 73 wherein the method further comprises:

combining the first program data with the data describing the integrated circuit layout to produce a second program data that describes a first corrected layout;

25

providing the second program data to a design rule checker apparatus;

and

operating the design rule checker apparatus to determine whether the first corrected layout falls within a set of integrated circuit design rules.

30

84. The photolithography mask of claim 73 wherein the first program data is provided on a computer readable media.

85. The photolithography mask of claim 73 wherein the operation comprises one of a group of operations including logical and arithmetic operations.

5

86. The photolithography mask of claim 73 wherein the first program data comprises data described by a GDS-II data file.

10

87. The photolithography mask of claim 73 wherein the first program data comprises data which corrects the layout for optical proximity effects.

15

88. The photolithography mask of claim 73 wherein the first program data comprises data which corrects the layout for a logical operation performed on the layout.

20

89. The photolithography mask of claim 88 wherein the logical operation comprises one of a group of logical operations including AND, NOT, OR, NOR and NAND.

90. The photolithography mask of claim 73 wherein the layout comprises one of a bright field and a dark field layout.


25

91. The photolithography mask of claim 73 wherein the layout comprises a phase shifting layout.


92. The photolithography mask of claim 73 wherein the method steps for performing the operation on the hierarchically described integrated circuit layout are executed by a machine in response to a program of instructions embodied in a program storage device readable by the machine.

1/19

100 - Simple Integrated Circuit Layout



110 - Hierarchical Representation of Layout



(Prior Art)
Figure 1





Figure 2






Figure 4

5/19




Figure 5

6/19

Generating a Delta Plane for Logical NOT Operation







Figure 6

7/19

Typical OPC Corrections

(Prior Art)
Figure 7(a)



(Prior Art)
Figure 7(b)

8/19




Figure 8

9/19




Figure 9




Figure 10(a)




Figure 10(b)

11/19

Generating a Delta Plane for OPC




Figure 11

12/19




Figure 12




Figure 13




Figure 14




Figure 15





Figure 16






Figure 18




Figure 19

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US98/19438

A. CLASSIFICATION OF SUBJECT MATTER

IPC(Cl.) : G03F 9/00; G06F 17/00, 17/50

US CL : 430/5, 22, 311; 364/488, 489, 490, 491; 395/500

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 430/5, 22, 311; 364/488, 489, 490, 491; 395/500

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

Please See Extra Sheet.

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y, P	US 5,705,301 A (GARZA et al) 06 January 1998, abstract, figures 1-2, 3-9, col 4, lines 20-67, col 5, lines 1-36, col 6, lines 33-52, col 7, lines 63-67, col 8, lines 1-8, col 8, lines 13-62, col 9, lines 55-67, col 10, lines 14-55, claims 1-7.	1-92
Y	US 5,538,815 A (OI et al) 23 July 1996, abstract, summary, figure 21.	1-92
A, P	US 5,801,954 A (LE et al) 01 September 1998, abstract, summary, figures 1-8, col 3-6.	1-92
A, P	US 5,702,848 A (SPENCE) 30 December 1997, see entire document.	1-92
A, P	US 5,740,068 A (LIEBMANN et al) 14 April 1998, see entire document.	1-92

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
E earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
I document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*Z* document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means	
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

16 NOVEMBER 1998

Date of mailing of the international search report

01 FEB 1999

Name and mailing address of the ISA US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

KEVIN TESKA

Telephone No. (703) 305-9704

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US98/19438

B FIELDS SEARCHED

Electronic data bases consulted (Name of data base and where practicable terms used):

APS, IEEE, GPIC

Search terms: optical proximity correction, opc, correct? layout, correct plane#, correct? data, design rule check###, drc, hierarchic? structure, hierarchic? tree, layout, gds###